

Screed

insulation

EPS FlooringTechnical Datasheet

Features:

- S and B EPS flooring offers excellent thermal performance providing savings in energy costs and higher comfort levels in dwellings.
- Maintains its thermal efficiency throughout the life of a building.
- · Highly cost effective floors.
- Rapid construction: no specialised equipment or trades required.
- Saves up to a week in building time when used in an all-dry system with flooring grade chipboard.
- Can be used under screeds, in heated floor slabs, below suspended slabs or between joists.
- Available in a variety of thicknesses.
- Non-toxic, non-irritant, moisture resistant, easy to cut and fix.
- A+ green guide rating

S and B EPS Flooring boards are available in the following grades:

EPS70

EPS

EPS100

Damp proof Membrane

EPS150

Blinded

Float Finish

EPS200

EPS250

EPS500

Lambdathem® 70

Lambdathem® ELITE

Factoria	Grades EPS							Lambdatherm®	
Features	EPS70	EPS100	EPS150	EPS200	EPS250	EPS500	70	ELITE	
Thermal Conductivity [k] value W/mk (10°C mean)	0.038	0.036	0.035	0.034	0.033	0.033	0.032	0.030	
Compressive Strength kPa Min (at 10% compressive strength)	70	100	150	200	250	500	70	100	
Cross Breaking Strength kPa Min	115	150	200	250	350	750	115	150	
Safe working load kPa at 1% nominal compression	21	45	70	90	100	190	21	45	
Vapour diffusion resistance factor µ1	20-40	30-70	30-70	40-100	40-100	40-100	20-40	30-70	
Vapour permeability omg [pa.h.m]	0.015 to 0.030	0.009 to 0.020	0.009 to 0.020	0.006 to 0.015	0.006 to 0.015	0.006 to 0.015	0.015 to 0.030	0.009 to 0.020	

S and B EPS flooring boards are designed for the insulation of ground floors in a variety of applications. The product is a CFC and HCFC free, lightweight, closed cell material which is easy to install. It has a high insulation value and allows for rapid dry construction methods to be used in new and renovated dwellings and is available in either square edge.



Identification / colour coding of products manufactured to BSEN 13163							
EPS 70E	2 x brown stripes & 1 red stripe						
EPS 100E	1 x black stripe & 1 red stripe						
EPS 120E	2 x green stripes & 1 red stripe						
EPS 150E	1 yellow stripe & 1 red stripe						
EPS 200E	2 x black stripes & 1 red stripe						
EPS 250E	1 violet stripe & 1 red stripe						
EPS 500E	1 x black, 1 green & 1 red						

	Flooring 2400 x 1200mm					
	Qty / Pack	Cu-m per pack	Sq-m per pack			
2400 x 1200 x 25mm	12	0.864	34.56			
2400 x 1200 x 30mm	10	0.864	28.8			
2400 x 1200 x 50mm	6	0.864	17.28			
2400 x 1200 x 75mm	4	0.864	11.52			
2400 x 1200 x 100mm	3	0.864	8.64			
2400 x 1200 x 150mm	2	0.864	5.76			

Feel free to contact us











0191 250 0818







